

Each AI unit is equipped as follow:

- * 2 AI Camera with CPU and network parts
- * 2 LED lights and speaker
- * Lock
- * Customer screen and creditcard reader
- * 5 shelves with pusher system on 4 shelves



MAIN FEATURES

- Cassette technology, placed on top of the cooler
- High-quality LED light (canopy & two (2) inner lighting)
- Large and smooth surfaces for branding
- Extended cooler width with bigger internal volume
- Low energy consumption
- Easy maintenance
- Environment-friendly refrigerant R290
- Electronic controller
- Door opening: reversible



TECHNICAL DETAILS

| | Celit MDC73 |
|------------------------------------|-----------------------|
| Net weight (kg) | 130 |
| Gross volume (l) | 601 |
| Net volume (l) | 486 |
| External dimensions W x D x H (mm) | 725 x 693 x 2000 |
| Internal dimensions W x D x H (mm) | 642 x 554 x 1645 |
| Power input W (220-240V, 50Hz) | 380 |
| Defrosting | Automatic |
| Lighting | 2 x vertical LED |
| Compressor | Danfoss |
| Refrigerant | R290 |
| Energy consumption (kWh/24h) | 5,9 |
| Evaporator type | Finned coil |
| Condenser type | AI Wingtube |
| Temperature control | Electronic thermostat |
| Door opening | Reversible |

TEMPERATURES

| | |
|--------------------------------|----------------------|
| Temperature range | +0°C to +6°C |
| Operating conditions min - max | +10°C to +25°C/55%RH |

SHELF DIMENSIONS

| | |
|------------------------------------|-----------|
| Adjustable shelf 1 W x D (mm) | 611 x 484 |
| Amount of adjustable shelves (pcs) | 5 |
| Bottom layer W x D (mm) | 642 x 530 |

TRANSPORTATION

| | |
|----------------------------------|------------------|
| Gross weight (kg) | 140 |
| Package size W x D x H (mm) | 780 x 710 x 2100 |
| Quantity in 20ft container (pcs) | 21 |
| Quantity in 40ft container (pcs) | 45 |
| Quantity in 13,6m truck (pcs) | 51 |

OPTIONS

| |
|------------------------------------|
| Full branding |
| Special color (RAL color system) |
| Stainless steel housing |
| Product dividers on shelves |
| Extra shelf |
| Energy Management Controller (EMC) |
| Smart Monitoring Interface (SMI) |

| | | | | | |
|--|-----------------------|-------------------|------------------|------------------|--|
| W x D x H W 725 mm D 693 mm H 2000 mm | HC R290 | 0.25 L 649 pcs | 0.5 L 387 pcs | 13.6 M 51 pcs | W x D x H W 780 mm D 710 mm H 2100 mm |
| KG 130 kg | RANGE +0°C to +6°C | 0.33 L 774 pcs | 0.33L 490 pcs | 40ft 45 pcs | KG 140 kg |